

DH-PFS3008-8GT-60

8-Port Unmanaged Desktop Switch with 4 Port PoE



System Overview

DH-PFS3008-8GT-60 is an unmanaged Desktop Switch with 4 × 10/100/1000 Mbps PoE Ports. It provides 8 × 10/100/1000 Mbps Ethernet ports. The product is equipped with two types of transmission modes (Extend Mode On/Extend Mode Off). The Orange port supports the Hi-PoE standards. It also supports PoE watchdog to avoid manually maintenance and device restart, which can realize the intelligent management and reduce the cost.

Functions

Intelligent PoE

Provides control over power consumption and offers real-time monitoring to ensure power supplies receive priority with important ports and to prevent malfunctions caused by changes in power consumption. Supports ultra wide power supplies and is able to adapt to IPC power fluctuations.

Hi-PoE 60W (Orange Port)

In addition to the IEEE802.3af and IEEE802.3at standards, orange port also supports a maximum power output of 60W for powering high-power devices.

PoE Watchdog

Adopts the innovative PoE Watchdog. PoE Watchdog can be switched on by dialing or turning on the WEB page switch. It enables the switch to automatically detect port status and restart failed ports to recover connection in case of IPC connection exception. This enables intelligent operation and maintenance management in its truest sense, effectively reducing manual maintenance costs.

Long Distance PoE

By dialing or enabling long-range transmission on the WEB interface, the transmission distance of a PoE port can be up to 250 m, meeting the requirements of wired transmission (bandwidth reduced to 10 Mbps).

All-Gigabit Ports

Designed with large buffer memory and all-Gigabit ports, enabling high-definition access of large stream.

- Intelligent PoE
- 8-pin assignment PoE power supply
- Long distance PoE
- PoE watchdog
- Hi-PoE 60W
- All-giga ports
- Wide working temperature



Scene

The device is applicable for use in different scenarios, including home, office, server farm, and small mall.

Technical Specification

Hardware

Data Transmission Port	Port 1-4: 4 × RJ-45 10/100/1000 Mbps (PoE) Port 5-8: 4 × RJ-45 10/100/1000 Mbps
Power Supply	48 V–57 V DC
Operating Temperature	–10 °C to +55 °C (+14 °F to +131 °F)
Operating Humidity	5%–95% (RH)
Storage Temperature	–20 °C to +70 °C (–4 °F to +158 °F)
Storage Humidity	5%–95% (RH)
Power Consumption	Idling: 3.0 W Full load: 60 W

Performance

Capacity	20 Gbps
Packet Forwarding Rate	11.9 Mpps
Packet Buffer Memory	1.5 Mbit
MAC Table Size	8K
Communication Standard	IEEE802.3; IEEE802.3u; IEEE 802.3ab; IEEE802.3X

PoE

PoE Standard	IEEE802.3af; IEEE802.3at; Hi-PoE
PoE Power	60 W
Power Consumption Management	Yes
PoE Pin Assignment	1, 2, 4, 5 (V+), 3, 6, 7, 8 (V-)
Long Distance PoE	Supports 250 m (820.21 ft)


General

Statics Protection	Air discharge: 8 kV Contact discharge: 6 kV
Thunder-proof	Common mode: 2 kV Differential mode: 0.5 kV
Net Weight	490 g (1.08 lb)
Product Dimensions	190 mm × 100 mm × 30 mm (7.48" × 3.93" × 1.18") (W × L × H)

Ordering Information

Type	Part Number	Description
PoE Switch	DH-PFS3008-8GT-60	Dahua 8-Port Unmanaged Desktop Switch with 4 Port PoE
	PFS3008-8GT-60	8-Port Unmanaged Desktop Switch with 4 Port PoE

Dimensions (mm[inch])



Panels

